

- Ferrite Chip Beads (0805 - A type)

Part Number		Impedance (Ω) @ 100MHz	DC Resistance (Ω) max	Rated Current (mA) max	Operating Temp.
FAM-N2-201209	-170	17 $\pm$ 25%	0.10	600	-25 $^{\circ}$ C to +85 $^{\circ}$ C
FAM-N4-201209	-800	80 $\pm$ 25%	0.30	400	
FAM-N1-201209	-121	120 $\pm$ 25%	0.30	300	
FAM-N2-201209	-121	120 $\pm$ 25%	0.30	300	
FAM-N1-201209	-151	150 $\pm$ 25%	0.30	300	
FAM-N4-201209	-221	220 $\pm$ 25%	0.50	250	
FAM-N1-201209	-301	300 $\pm$ 25%	0.50	250	
FAM-N2-201209	-401	400 $\pm$ 25%	0.50	250	
FAM-N1-201209	-601	600 $\pm$ 25%	0.60	200	
FAM-N4-201209	-102	1000 $\pm$ 25%	0.80	100	
FAM-N4-201209	-222	2200 $\pm$ 25%	1.00	100	
FAM-N4-201209	-272	2700 $\pm$ 25%	1.50	100	

Test instrument: HP 4291B LCR meter

